

(19)



Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11)

**EP 1 280 363 A2**

(12)

**EUROPEAN PATENT APPLICATION**

(43) Date of publication:  
29.01.2003 Bulletin 2003/05

(51) Int Cl.7: **H04Q 1/06**, **H04Q 1/10**,  
**H05K 7/00**

(21) Application number: **02254913.3**

(22) Date of filing: **12.07.2002**

(84) Designated Contracting States:  
**AT BE BG CH CY CZ DE DK EE ES FI FR GB GR**  
**IE IT LI LU MC NL PT SE SK TR**  
Designated Extension States:  
**AL LT LV MK RO SI**

(30) Priority: **26.07.2001 US 916923**

(71) Applicant: **Panduit Corporation**  
**Tinley Park, Illinois 60477-3091 (US)**


(72) Inventors:  
• **Barker, Jed M.**  
**Orland Park, Illinois 60467 (US)**  
• **Honan, Kevin E.**  
**Tinley Park, Illinois 60477 (US)**  
• **Donnell, Mark J.**  
**Orland Park, Illinois 60462 (US)**

(74) Representative: **Roberts, Gwilym Vaughan et al**  
**KILBURN & STRODE,**  
**20 Red Lion Street**  
**London WC1R 4PJ (GB)**

**(54) Angled patch panel with cable support bar for network cable racks**

(57) A patch panel (100) mountable to a network rack (500) includes a frame (110) and rack mounting plates (130). The frame (110) forms a central section having a longitudinal width sized to fit within the network rack (500), a predefined height, a front side, and a rear side. The rack mounting plates are provided on opposite longitudinal ends of the central section and allow the panel (100) to be mounted to a network rack (500). The central section is angled outwardly in an inverted V-shape. The central section has mountable thereon a plurality of cable connectors (400) that receive cabling (540) on the front side and the rear side of the patch panel frame (110). When mounted, the plurality of cable connectors (400) are oriented to have rear surfaces thereof face a common axis of the central section. This

provides front connector surfaces that are better oriented relative to front side cabling which is provided along vertical cable managers or ducts (530) near front edges of the rack (500) rails. This orientation provides a more natural flow of cables (540) entering the patch panel (100) and reduce bending angles to less than 90°, which reduces or eliminates the need for external horizontal cable management on the front side of the patch panel (100) while maintaining adequate bend radius control. Moreover, the angled frame (110) provides an angled surface that has increased port capacity as compared to a conventional flat-faced patch panel and has an increased volume behind the panel for receiving and housing cabling. A support bar (200) may be provided on the rear side of the patch panel to support the weight of the exiting cabling.

**FIG. 3**

## Description

[0001] Generally, the present invention relates to cable management devices for network equipment racks. In particular, the invention relates to an angled patch panel and cable support bar therefor.

[0002] Cables, such as UTP, ScTP, coaxial and fiber optic cables, transmit data, voice, video and/or audio information in the telecommunications industry. Patch panel or network equipment enclosure and rack systems are well-known in the industry. They manage and organize such cables both to and from such equipment and/or to and from cross-connect systems. These systems usually include the standard EIA 19", 23" or other distribution frame rack on which one or more patch panels, network equipment, fiber optic enclosures and the like are mounted. Rack enclosures serve various functions, including their use as slack trays, splice trays, cable organizers and patch panels. These racks also serve as interconnect or cross-connect enclosures when they interface with equipment. Additionally, these racks may serve as a telecommunications closet, allowing the cables to be terminated, spliced, patched and/or stored at various places along their length.

[0003] The rack is usually formed from a frame having mounting apertures located along the vertical legs or walls of the rack. Patching equipment, such as a patch panel, is mounted onto the rack so as to generally define a patching side, where patch cords from another active device or another patch panel can be cross-connected and interconnected, and a distribution side, where cables from network equipment and/or work station areas are terminated. Generally, some form of cable management is provided on both sides of the rack to support and route the cables. While preventing detrimental bending is always important even for copper cabling, with the increasing use of fiber optic connectors as applied to connector rack systems, proper cable management and bend radius control has become increasingly important. Many known systems are unable to provide complete bend radius control, are inefficient, are difficult to manufacture, are difficult to manage and access, and/or have other drawbacks. Thus, improvement in the cable management of network rack systems is desired. In particular, many patch panel systems require both horizontal and vertical cable management within the rack.

[0004] There is a need for a patch panel design that eliminates the necessity for one or more of these external cable management devices.

[0005] There is also a need for a patch panel system that can accommodate more port capacity and provide additional space for containing cabling.

[0006] It is an object of the invention to provide an improved patch panel for a network rack that can provide better cable management without the need for a horizontal cable manager.

[0007] It is another object of the invention to provide an improved patch panel that can accommodate greater

port capacity.

[0008] It is another object of the invention to provide cable support to a patch panel.

[0009] Various ones of the above and other objects are achieved by a patch panel mountable to a network rack comprising a frame and rack mounting plates. The frame forms a central section having a longitudinal width sized to fit within the network rack, a predefined height, a front side, and a rear side. The rack mounting plates are provided on opposite longitudinal ends of the central section and allow the panel to be mounted to a network rack. The central section is angled outwardly in an inverted V-shape. The central section has mountable thereon a plurality of cable connectors that receive cabling on the front side and the rear side of the patch panel frame. When mounted, the plurality of cable connectors are oriented to have rear surfaces thereof face a common axis of the central section.

[0010] Various ones of the above and other objects are also achieved by a network rack and patch panel assembly, comprising: a network rack having two rails spaced a predetermined distance from each other, each rail including spaced mounting openings; and a patch panel mounted to the network rack. The patch panel includes a frame forming a central section and having a longitudinal width sized to fit between the two rails, a predefined height, a front side, and a rear side. The patch panel also includes rack mounting plates provided on opposite longitudinal ends of the central section connected to ones of the spaced mounting openings of the rails. The central section is angled outwardly in an inverted V-shape. Mounted on the central section are a plurality of cable connectors that receive cabling on the front side and the rear side of the patch panel frame. The plurality of cable connectors are oriented to have rear surfaces thereof face a common axis of the central section.

[0011] The patch panel and rack may further include a cable support bar that supports the weight of cabling exiting the rear of the patch panel.

[0012] Embodiments of the invention will now be discussed by way of example with reference to the drawings, of which:

Fig. 1 shows an exploded isometric view of a first embodiment of an angled patch panel according to the present invention and a cable support bar therefor;

Fig. 2 shows a top view of the patch panel of Fig. 1; Fig. 3 shows an exploded view of an insert module loaded with four cable connector modules being inserted into the patch panel of Fig. 1;

Fig. 4 shows the patch panel of Fig. 1 and the cable support bar loaded onto a 19" standard rack;

Fig. 5 is a detailed partial view of the 19" standard rack of Fig. 4;

Fig. 6 shows a top view of the patch panel and the 19" standard rack of Fig. 4;

Fig. 7 show an isometric view of a second embodiment of an angled patch panel according to the present invention;

Fig. 8 shows the insert modules used in the second embodiment of the patch panel; and

Fig. 9 shows an exploded view of an insert module loaded with four cable connector modules being loaded into the second embodiment of the patch panel.

[0013] A patch panel 100 according to an exemplary first embodiment of the invention is generally shown in Figs. 1-6 and is useful in providing a support panel for mounting reconfigurable ports for patching components in a network rack.

[0014] The patch panel 100 includes an outwardly angled central frame 110, a plurality of faceplate openings 120 and a mounting plate 130 at each end with a plurality of mounting apertures 135, as shown in Fig. 1. A flat centerpiece 140 located midway along frame 110 may be provided to space the openings 120 on opposite halves of the central frame 110 from each other. This centerpiece 140 also slightly reduces the depth D of the patch panel by eliminating the angle at a central portion where no openings 120 are located. Patch panel 100 is preferably formed of a suitable material, such as metal so as to be self grounding. However, when a separate grounding bar is available, frame 110 may be formed of any suitable rigid material, such as many plastics or composites. A separate or integral cable support bar 200 may be provided on a rear side of the patch panel. Cable support bar 200 includes a bar portion 210 and mounting plates 220.

[0015] Both the patch panel 100 and cable support bar 200 are designed to mount on a rack. Patch panel 100 can be any size, but preferably is sized with a width W to fit within a conventional 19" or 23" EIA network rack that has spaced vertical rails or legs 510 that allow the mounting of various rack elements thereon (see Figs. 4-5). The patch panel can occupy a single rack unit height of 1.75" (4.45 cm) or multiple rack unit height, such as the two rack unit height illustrated (3.5" or 8.9 cm). The rack 500 should have various mounting openings 520 or comparable devices to facilitate equipment mounting. When mounted, patch panel 100 protrudes out from the front of the rack 500 by a distance D of several inches, as shown in Figs. 2 and 6, due to the outwardly angled frame 110.

[0016] The invention is not limited to such EIA racks, but is equally applicable to other known or subsequently developed racks. Moreover, a network rack 500 need not be an open frame structure as in the above EIA racks, but may include mounting cabinets or enclosures having mounting features and walls defining openings that can receive and affix rack elements, such as the patch panel 100, cable managers and the like.

[0017] Patch panel 100 is angled outwardly in a generally inverted V-shape. Fig. 2 shows a top view of the

angled patch panel 100. Each half of the patch panel frame 110 is preferably a mirror image and angled from the other by an angle  $\phi$ , which is an obtuse angle of a suitable angle of between about 90° and 180°, preferably an angle of between about 100° to 140°, and more preferably between about 110° and 130°. The illustrative embodiment shown has an angle  $\phi$  of about 120°. This allows cables attached to the front of the patch panel to flow directly to one or more vertical cable managers located adjacent the network rack.

[0018] The patch panel frame halves are also angled relative to mounting brackets 130 (which are oriented in line with each other and parallel to the front sides of rails 510 of the mounting rack 500) at an angle of  $\theta$ , which is an acute angle of preferably not more than 45°, preferably between about 20° to 40° degrees, and more preferably between about 25° and 35°. In the illustrative example, the angle  $\theta$  is about 30°. While the central section is shown and described as being symmetrical, it is to be understood that the patch panel sections 110 could be disposed at different angles relative to the brackets 130 and thus be of different lengths.

[0019] Patch panel 100 has a plurality of faceplate openings 120 that receive insert modules 300, as shown in Fig. 3. The insert modules 300 are sized to fit within openings 120, preferably by snap fit. However, rather than replaceable modules, modules 300 may be integrated into frame 110. The modules and openings may be multiple rack unit heights or may be sized as a single rack unit height, as shown. In the first illustrative exemplary embodiment, patch panel 100 has twelve faceplate openings 120. These twelve faceplate openings 120 allow twelve insert modules 300 to be inserted into the patch panel 100, as shown in Fig. 3.

[0020] Insert modules 300 are fitted to hold one or more removable cable connector modules 400. Cable connector modules 400 may take many forms, such as electrical, optical, telecommunications-related or other known or subsequently developed connector for connecting cabling. Preferred modules are capable of connecting UTP, ScTP, coaxial and/or fiber optic cables used in the telecommunications industry to transmit data, voice, video and/or audio information.

[0021] Insert modules 300 are secured within patch panel openings 120 by way of snap fit, as is known in the art. Fig. 3 shows an exploded view of an insert module 300 loaded with four cable connector modules 400 that is then inserted into patch panel 100. Three other insert modules 300 with cable connector modules 400 are already loaded into patch panel 100. In this first illustrative example of Figs. 1-6, patch panel 100 can have a total of twelve insert modules 300, each with a capacity of four connector modules 400 for a total capacity of 48 ports in a two rack unit space.

[0022] There are several advantages to the inventive patch panel. By making the frame angled outwardly in an inverted V-shape, the cable connector modules when inserted into the openings all face a common central ax-

is (parallel to the depth direction D). This provides front connector surfaces that are better oriented relative to front corners of the rack rails 510, where vertical cable managers or ducts 530 are provided that contain cables 540 that mate with front sides of various ones of the cable connector modules 400 as shown in Fig. 6. In particular, the angled frame 110 provides a connector surface that is at a reduced angle relative to an exit direction of the cables exiting the vertical cable manager as compared to conventional patch panels. That is, prior art, flat-faced patch panels were located substantially parallel to the exit direction and required a 90° cable bend for connection. This requires an external horizontal cable manager to control the bend and provide a minimum bend radius. However, as the inventive patch panel has surfaces that intersect this exit direction (direction X in Fig. 6) at a strong acute angle, the bend necessary to achieve connection is substantially less than 90° as shown. This reduces or eliminates the need for additional horizontal cable management to guide exiting cables from the vertical cable managers 530 to the patch panel 100 as the cables 540 more naturally flow from the vertical ducts 530 to the individual connector modules 400.

**[0023]** Additionally, this structure results in slightly shorter patch cable lengths than before. Moreover, the outwardly angled frame 110 provides increased space behind patch panel 100 for housing the cabling. That is, as shown in Fig. 6, a conventional flat-faced patch panel would be flush to the rack rails 510 and would thus only provide an area of the inner rectangle between rails 510. However, with the angled patch panel, the receiving area is this inner rectangle plus the triangular area defined by the outwardly extending frame of patch panel 100.

**[0024]** Further, by making the front face of the patch panel angled (in an inverted V-shape), rather than flat, there is additional surface area on the front face of the patch panel that allows for increased port capacity for the patch panel. That is, for a rack of a given width, such as 19", a conventional flat patch panel would only have a surface area equal to  $19" \times N \times 1.75"$ , where N is the number of rack units in height. However, at any given angle  $\theta$ , the total length of the two angled halves of frame 110 will be greater than the length of a corresponding flat piece. For example, with the inventive angled patch panel front face at an exemplary angle  $\theta$  of 30°, the surface area is approximately  $22" \times N \times 1.75"$ . This and other surface areas for other angles  $\theta$  can be simply solved using basic trigonometric principles.

**[0025]** The aforementioned features work together to increase the functionality of the inventive patch panel. That is, the increased space behind the patch panel helps accommodate the cabling needs resulting from the increased port capacity due to the extra patch panel surface area, and the uniformly angled connector modules better manage the cabling on the front side of the patch panel by reducing the necessary bend angle for incoming cabling, eliminating the need for external horizontal cable managers as often required with conven-

tional patch panels.

**[0026]** While horizontal cable management on the front side may not be necessary, it may be beneficial to provide cable support bar 200 to assist in supporting the weight of the various cabling attached to the rear side of patch panel 100, and to assist in the direction of the cables exiting patch panel 100. Cable support bar 200 is preferably formed of a suitable material, such as metal. Support bar portion 210 preferably extends the entire width of rack 500 and includes mounting plates 220 each with at least one mounting aperture 225 as shown to mount the support bar on rack 500 or comparable device.

**[0027]** Cable support bar 200 is preferably separate from patch panel 100, but may be integrally formed therewith if desired. Cable support bar 200 may be attached to rack 500 using mounting apertures 225 either from the front when the patch panel 100 is attached, or from the back after the patch panel 100 has been attached. Attaching the cable support bar 200 from the back allows the end user to install the cable support bar 200 after all of the connectors have been terminated, thus eliminating any interference from the cable support bar 200 when terminating the connectors.

**[0028]** In a second embodiment of the present invention shown in Figs. 7-9, a variation in configuration is provided. Patch panel 700 is angled with angles  $\phi$  and  $\theta$  as in the first illustrative embodiment. However, for this embodiment, there are only six faceplate openings 720 in frame 710 that allow for twelve pack insert modules 800 to be inserted therein. These modules occupy a double rack height. Like the previous embodiment, mounting plates 730 are provided for mounting the patch panel to a rack and a flat centerpiece 740 may be provided.

**[0029]** The twelve-pack insert modules 800 for the second embodiment of the present invention are shown in Fig. 8. While more or less connector modules could be provided, the illustrative insert modules 800 are capable of receiving up to twelve single-spaced cable connector modules 900. To allow a snap fit within openings 720, insert modules 800 have four 'upside down' snaps 810, as shown in Fig. 8, which hold insert module 800 to patch panel 700. However, other methods of affixing insert modules 800 to openings 720 are contemplated.

**[0030]** Fig. 9 shows an exploded view of an insert module 800 loaded with four exemplary cable connector modules 900 being positioned for mounting into patch panel 700. Five other insert modules 800 with cable connector modules 900 are shown already loaded into patch panel 700. While not necessary, the illustrative patch panel 700 covers two rack units as in the previous embodiment and fits into a standard 19" network rack. With this configuration, a capacity of 72 cable connector ports can be achieved in a two rack height patch panel.

**[0031]** As in the previous embodiment, frame 710 is angled outwardly in an inverted V-shape so that the rear of all of the ports are angled toward a common central

axis. This provides better flow of the cabling entering the front of patch panel 700 as described with respect to the first embodiment to eliminate the need for a front external horizontal cable manager. However, as in the first embodiment, a cable support bar 200 may be provided to support the weight of exiting cables to the rear of patch panel 700.

**[0032]** While the invention has been shown and described in conjunction with specific exemplary embodiments, the invention is not limited to these. It will be obvious to those skilled in the art that changes and modifications may be made without departing from the teachings of this invention and that the matter set forth in the foregoing description and accompanying drawings is offered by way of illustration only and not as a limitation. The actual scope of the invention is intended to be defined in the following appended claims.

### Claims

1. A patch panel mountable to a network rack, comprising:

a frame forming a central section and having a longitudinal width sized to fit within the network rack, a predefined height, a front side, and a rear side; and

rack mounting plates provided on opposite longitudinal ends of the central section,

wherein the central section is angled outwardly in an inverted V-shape, the central section having mountable thereon a plurality of cable connectors that receive cabling on the front side and the rear side of the patch panel frame, the plurality of cable connectors when mounted being oriented to have rear surfaces thereof face a common axis of the central section.

2. The patch panel according to claim 1, wherein the common axis of the central section is located at a midpoint of the central section.
3. The patch panel according to claim 1, wherein the frame includes at least one faceplate opening.
4. The patch panel according to claim 3, wherein at least two faceplate openings are provided, one on each side of the common axis of the central section.
5. The patch panel according to claim 3 or 4, further comprising at least one removable insert module, for example two, sized to fit within said at least one faceplate opening, the at least one removable insert module containing at least one of the plurality of cable connectors, and preferably wherein the at least one removable insert module is snap fittable to the

at least one faceplate opening, and preferably wherein the plurality of cable connectors connect to at least one of UTP, ScTP, coaxial and fiber optic cables.

6. The patch panel according to claim 5, wherein six faceplate openings are provided, three on each side of the common axis of the central section, and preferably wherein each faceplate opening includes at least one removable insert module and each insert module receives twelve cable connectors.

7. The patch panel according to claim 5, wherein twelve faceplate openings are provided, six on each side of the common axis of the central section, and preferably wherein each faceplate opening includes at least one removable insert module and each insert module receives four cable connectors.

8. The patch panel according to claim 1, wherein the central section of the frame has two angled panel sections, each angled relative to the other by an obtuse angle  $\Phi$  of between  $90^\circ$  and  $180^\circ$ , preferably between  $100^\circ$  to  $140^\circ$ , more preferably between  $110^\circ$  to  $130^\circ$ , most preferably about  $120^\circ$ , and/or wherein the two panel sections are the same length, or wherein the central section includes a flat center-piece at the intersection of the two angled panel sections.


9. A patch panel assembly for a network rack comprising the patch panel of claim 1 and a cable support bar mountable to the rear of the patch panel.


10. The patch panel assembly of claim 9, wherein the cable support bar includes a bar portion having a longitudinal width sized to fit within the network rack and rack mounting plates at longitudinal ends of the bar portion.

11. A network patch and patch panel assembly, comprising:

a network rack having two rails spaced a predetermined distance from each other, each rail including spaced mounting openings; and a patch panel as claimed in any of claims 1 to 8 mounted to the network rack, the frame having a longitudinal width sized to fit between the two rails; and the rack mounting plates being connected to ones of the spaced mounting openings of the rails.


12. The network rack and patch panel assembly of claim 11 further comprising a cable support bar mounted between the rack rails.






BEST AVAILABLE COPY


FIG. 3








BEST AVAILABLE COPY




BEST AVAILABLE COPY


FIG. 6



AVAILABLE COPY


FIG. 7





BEST AVAILABLE COPY

FIG. 9





(12) **EUROPEAN PATENT APPLICATION**

(88) Date of publication A3:  
**05.01.2005 Bulletin 2005/01**

(51) Int Cl.7: **H04Q 1/06, H04Q 1/10,  
H05K 7/00, H01R 13/518**

(43) Date of publication A2:  
**29.01.2003 Bulletin 2003/05**

(21) Application number: **02254913.3**

(22) Date of filing: **12.07.2002**

(84) Designated Contracting States:  
**AT BE BG CH CY CZ DE DK EE ES FI FR GB GR  
IE IT LI LU MC NL PT SE SK TR**  
Designated Extension States:  
**AL LT LV MK RO SI**

(72) Inventors:  
• **Barker, Jed M.**  
**Orland Park, Illinois 60467 (US)**  
• **Honan, Kevin E.**  
**Tinley Park, Illinois 60477 (US)**  
• **Donnell, Mark J.**  
**Orland Park, Illinois 60462 (US)**

(30) Priority: **26.07.2001 US 916923**


(71) Applicant: **Panduit Corporation**  
**Tinley Park, Illinois 60477-3091 (US)**

(74) Representative: **Roberts, Gwilym Vaughan et al**  
**Kilburn & Strode**  
**20 Red Lion Street**  
**London WC1R 4PJ (GB)**

(54) **Angled patch panel with cable support bar for network cable racks**

(57) A patch panel (100) mountable to a network rack (500) includes a frame (110) and rack mounting plates (130). The frame (110) forms a central section having a longitudinal width sized to fit within the network rack (500), a predefined height, a front side, and a rear side. The rack mounting plates are provided on opposite longitudinal ends of the central section and allow the panel (100) to be mounted to a network rack (500). The central section is angled outwardly in an inverted V-shape. The central section has mountable thereon a plurality of cable connectors (400) that receive cabling (540) on the front side and the rear side of the patch panel frame (110). When mounted, the plurality of cable connectors (400) are oriented to have rear surfaces thereof face a common axis of the central section. This provides front connector surfaces that are better oriented relative to front side cabling which is provided along vertical cable managers or ducts (530) near front edges of the rack (500) rails. This orientation provides a more natural flow of cables (540) entering the patch panel (100) and reduce bending angles to less than 90°, which reduces or eliminates the need for external horizontal cable management on the front side of the patch panel (100) while maintaining adequate bend radius control. Moreover, the angled frame (110) provides an angled surface that has increased port capacity as compared to a conventional flat-faced patch panel and has an increased volume behind the panel for receiving and housing cabling. A support bar (200) may be provided

on the rear side of the patch panel to support the weight of the exiting cabling.



**FIG. 3**



European Patent  
Office

# EUROPEAN SEARCH REPORT

Application Number  
EP 02 25 4913

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (InCl.7)
X	EP 0 508 870 A (DIGITAL EQUIPMENT CORP) 14 October 1992 (1992-10-14) * column 6, line 35 - column 7, line 15 *	1-12	H04Q1/06 H04Q1/10 H05K7/00 H01R13/518
A	WO 99/63628 A (ADC TELECOMMUNICATIONS INC) 9 December 1999 (1999-12-09) * figure 1 *		
A	WO 00/28363 A (NOLF JEAN MARIE ETIENNE ; RAYCHEM SA NV (BE); WAMBEKE ALAIN (BE); BRAN) 18 May 2000 (2000-05-18)		
A	US 3 846 590 A (MCLAIN T) 5 November 1974 (1974-11-05)		
A	DE 42 34 386 A (SIEMENS AG) 17 June 1993 (1993-06-17)		
			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
			H04Q H01R
The present search report has been drawn up for all claims			
Place of search The Hague		Date of completion of the search 15 November 2004	Examiner Vandevenne, M
CATEGORY OF CITED DOCUMENTS		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	
X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document			

EPO FORM 1503 03 82 (P04C01)



**ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.**

EP 02 25 4913

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

15-11-2004

Patent document cited in search report		Publication date		Patent family member(s)	Publication date
EP 0508870	A	14-10-1992	US	5129842 A	14-07-1992
			EP	0508870 A1	14-10-1992
			JP	5129045 A	25-05-1993
-----					
WO 9963628	A	09-12-1999	US	6537106 B1	25-03-2003
			AT	246851 T	15-08-2003
			AU	743265 B2	24-01-2002
			AU	4006099 A	20-12-1999
			BR	9910906 A	13-02-2001
			CA	2334152 A1	09-12-1999
			CN	1304569 T	18-07-2001
			DE	69910204 D1	11-09-2003
			DE	69910204 T2	17-06-2004
			EP	1084523 A1	21-03-2001
			ES	2207219 T3	16-05-2004
			HK	1040572 A1	24-12-2003
			JP	2002517890 T	18-06-2002
			NZ	508811 A	28-02-2003
			TW	423184 B	21-02-2001
			WO	9963628 A1	09-12-1999
			US	2003129871 A1	10-07-2003
-----					
WO 0028363	A	18-05-2000	CN	1325498 T	05-12-2001
			EP	1127286 A1	29-08-2001
			WO	0028363 A1	18-05-2000
-----					
US 3846590	A	05-11-1974	NONE		
-----					
DE 4234386	A	17-06-1993	DE	9115668 U1	20-02-1992
			DE	4234386 A1	17-06-1993
			CH	684228 A5	29-07-1994
-----					

EPO FORM P0453

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

**THIS PAGE BLANK (USPTO)**